



Apparatus and Method for Controlling Battery Temperature of a Power Supply for an Electrical Device

Sheet 1 of 7




JP9 2000 0347
Apparatus and Method for Controlling Battery Temperature of a
Power Supply for an Electrical Device

Sheet 2 of 7




JP9 2000 0347
 Apparatus and Method for Controlling Battery Temperature of a
 Power Supply for an Electrical Device

Sheet 3 of 7



JP9 2000 0347
Apparatus and Method for Controlling Battery Temperature of a
Power Supply for an Electrical Device

Sheet 4 of 7



Apparatus and Method for Controlling Battery Temperature of a Power Supply for an Electrical Device


Sheet 5 of 7

Thermal level	5		4		3	
Action	Power off		Suspend		Throttling	
Location	enable	disable	enable	disable	enable	disable
TH1	65 degC	N/A	60 degC	52 degC	55 degC	50 degC
TH2	110 degC	N/A	105 degC	95 degC	100 degC	90 degC
TH3	55 degC	N/A	50 degC	42 degC	45 degC	40 degC


2		1		0	
Clock down		Rotate fan		Normal state	
enable	disable	enable	disable	enable	disable
53 degC	48 degC	50 degC	40 degC	N/A	N/A
95 degC	85 degC	90 degC	60 degC	N/A	N/A
42 degC	38 degC	38 degC	35 degC	N/A	N/A

Apparatus and Method for Controlling Battery Temperature of a
Power Supply for an Electrical Device

Sheet 6 of 7



(a)



(b)

